



3M IJ-35C

4mil Pressure Sensitive Adhesive Vinyl — 3M Comply™ Air Release

Calendered white opaque vinyl with gray pressure-sensitive adhesive and Comply air-release channels for fast, bubble-free installs. Ideal for windows, walls, retail and short- to medium-term outdoor graphics.

Environment: Indoor & Outdoor | **Print sides:** Single-sided
Size: Custom size (up to 52" roll width) | **Longevity:** Short to medium-term

COMMON USES	OPTIONS
• Windows • Walls • Promotions • Retail • Event graphics	• Contour cut • Gloss, matte or no laminate • Custom size

TECHNICAL DATA — PHYSICAL / APPLICATION

PROPERTIES	
Adhesive system	Pressure-sensitive with Comply™ adhesive — bubble-free installs
PHYSICAL CHARACTERISTICS	
Material	Vinyl
Color	White opaque
Film thickness (without adhesive)	3.2 mil (0.081 mm)
Film thickness (with adhesive)	4.0 mil (0.102 mm)
Adhesive type	Pressure-sensitive
Adhesive color	Gray
Liner	Polycoated paper
APPLICATION CHARACTERISTICS	
Surface type	Smooth, flat and simple curved surfaces
Substrate type	Metal, rigid plastic and painted substrates
Application temperature	Air and substrate 40° to 100°F (4° to 38°C)
Application method	Dry

Finished graphic exposure temperature	−59° to +192°F (−50° to +90°C)
Graphic removal	Permanent
EXPOSURE TYPES	
U.S. Vertical Exposure	Face of graphic is ±10° from vertical
Print	UV / solvent / latex compatible (verify ink set)



Specifications are for guidance based on typical substrate data. Confirm final specs with Signs Fast & Affordable when ordering. High-resolution print-ready artwork recommended. Contour / custom cut paths must be reviewed on design-service jobs.